

A close-up, low-angle shot of a running shoe's sole, showing a complex tread pattern of black rubber lugs. The shoe is white with red accents. It is positioned on a patch of bright green grass. The background is a blurred green field, suggesting an outdoor setting. The overall lighting is bright and natural.

**AXEL**

# **solutions for polyurethanes**

**internal & external mold releases**

Manufacturers of advanced polyurethane products understand the importance of delivering finished goods with superior structural and surface quality. Our PU releases are designed to keep molds running cleaner for longer, reducing downtime and enhancing productivity.

# solutions for polyurethanes

	Product Type	Product Name	Description	Application	Type of Mold
External Mold Releases	Semi-Permanent Solvent-based	XTEND® 19RSS	Long lasting release. Recommended for rigid foams and elastomers.	Wipe or spray on molds up to 310°F/154°C. Can be used to mold up to 400°F/205°C.	All
	Semi-Permanent Water-based	XTEND® W-7806R	Long lasting release. Not recommended for applications that require paint.	Wipe or spray on. Stable to 400°F/205°C.	All
	Polymeric Solvent-based	MoldWiz® 435PU Series	High performance PU release. Non-silicone. Quick drying. Available in different strengths.	Wipe or spray on at ambient to hot molds.	All
		MoldWiz® 462EPU	Highest performance PU release.	Wipe or spray on at ambient to hot molds.	All
	Polymeric Water-based	MoldWiz® EM-606SFL	Quick drying, general purpose release with good slip.	Wipe or spray on at temperatures up to 310°F/154°C. Can be used to mold up to 400°F/205°C.	All
		MoldWiz® FFIH-85	Film forming release adheres to foam part. Can be painted.	Preferably spray on at ambient temperatures. Can also be brushed on.	All
	Solvent-based	PasteWiz® HC	Easy to use paste wax.	Wipe on and polish.	All including porous

	Product Name	Description
Internal Mold Releases	MoldWiz® INT-1230	General purpose release-foam for elastomers and non-aqueous in-mold coatings.
	MoldWiz® INT-120IMC	Release additive for in-mold coatings and polyureas.
	MoldWiz® INT-EPH19	Release additive for waterborne polyureas.
	MoldWiz® INT-1681OG	Release for optical grade cast PU.
	MoldWiz® INT-1968RAC MoldWiz® INT-1948MCH	For aromatic polyurethane pultrusion.
	MoldWiz® INT-1968RAC MoldWiz® INT-1960MCH	For aliphatic polyurethane pultrusion.
	MoldWiz® INT-1940RTM	Release additive for RTM, infusion, or other closed-molded PU processes.
	MoldWiz® INT-1944NRR	Suitable for pultrusion, infusion, or RTM when no change to gel time is required.

This information is supplied for technically skilled professionals working at their own risk. AXEL believes the information to be accurate, although the Company assumes no liability in the validity of the information for any specific process or application. Please refer to individual data sheets for further application, safety, and handling information. MoldWiz®, XTEND®, PasteWiz®, and CleanWiz® are registered trademarks of Axel Plastics Research Laboratories, Inc. © 2022, Axel Plastics Research Laboratories, Inc. All Rights Reserved. Rev Mar 2022.

50 Cambridge Drive | Monroe, Connecticut 06468 US  
800.332.AXEL | info@axelplastics.com | axelplastics.com



www.axelplastics.com  
800.332.AXEL