



TABLE OF CONTENTS

VACUUM PLUGS

1

PIPES

1

- FOR AUTOCLAVES
- FOR OVENS

PLUGS & ADAPTERS

2

- QUICK PLUGS
- OTHER PLUGS & ADAPTERS

ANCILLARIES & TOOLS

4

- VACUUM REGULATION
- INFRARED THERMOMETER
- LEAK DETECTOR
- ELECTRIC SCISSORS

BONDING EQUIPMENT

4

- AUTOCLAVES
- HOT DRAPE FORMERS
- HOT BONDERS
- IR LAMPS

VACUUM MOULDING ANCILLARIES

VACUUM PLUGS



1. QUICK SELF-CUTTING VACUUM PLUG -1/4" MALE
 Red silicone seal
 Blue anodized nut
 The film is not entirely cut so that the opercule does not go away

ACPRISE-VIDEAUTO1/4M

2. QUICK VACUUM PLUG 1/4" MALE
 Silicone seal (no rotation)
 Anodized nut

ACPRISE-VIDE1/4M

EXAMPLES



TUBES

SILINOX



PTFE pipe
 + Steel braid + Spring

REFERENCE

REFERENCE	length	temperature	pressure
ACTUB-SILINOX10A0100	1 m	220°C	14 bar int.& ext.
ACTUB-SILINOX10A0200	2 m		
ACTUB-SILINOX10A0300	3 m		
ACTUB-SILINOX10A0400	4 m		
ACTUB-SILINOX10A0600	6 m		
ACTUB-SILINOX10A0800	8 m		
ACTUB-SILINOX10A1000	10 m		
ACTUB-SILINOX10A1200	12 m		



1/4" G Connector

Ø int. 10 mm
 Ø ext. 18 mm

Others crimpings
 on request

Silicone TUBES



SILICONE
 pipe +
 Spring



SILICONE
 Pipe

REFERENCE

REFERENCE	Ø int.	Ø ext.	length	temperature	pressure
ACTUB-SILR10-18	10 mm	18 mm	5 ml max.	200°C	3 bar ext.
ACTUB-SIL04-08	4 mm	8 mm	25 ml reel	220°C	-
ACTUB-SIL06-12	6 mm	12 mm		220°C	
ACTUB-SIL07-13	7 mm	13 mm		220°C	
ACTUB-SIL09-16	9 mm	16 mm		220°C	
ACTUB-SIL10-18	10 mm	18 mm		220°C	
ACTUB-SIL10-23	10 mm	23 mm		220°C	

VACUUM MOULDING ANCILLARIES

PLUGS & ADAPTERS

QUICK PLUGS



Unit

AUTOCLAVE



NAME

REF.



QUICK MALE PLUG
1/4 G I with shut-off valve

ACAUTO-M-1/4M

240 °C



QUICK FEMALE PLUG
1/4 G I with shut-off valve

ACAUTO-M-1/4F

240 °C



QUICK MALE PLUG
1/2 G I with shut-off valve

ACAUTO-M-1/2M

240 °C



QUICK FEMALE PLUG
3/8 F I with shut-off valve

ACAUTO-F-3/8F

210 °C



QUICK PLUG FOR TUBE
10 mm

ACAUTO-F-TUB10M

210 °C

STANDARD



NAME

REF.



QUICK MALE PLUG
1/4 G I with shut-off valve

ACAUTOECO-M-1/4F

210 °C



QUICK FEMALE PLUG
1/4 G I with shut-off valve
Viton seal + PTFE

ACAUTOECO-F-1/4F

210 °C



capacity



length



width



packaging



thickness



weight



color



temperature

VACUUM MOULDING ANCILLARIES

OTHER PLUGS & ADAPTERS

Y Plugs



NAME	REFERENCE
DOUBLE Y PLUG - 1/4"F	ACRAC-Y1/4F
DOUBLE Y PLUG - 3/8"F	ACRAC-Y3/8F



Unit

X Plugs



NAME	REFERENCE
TRIPLE X PLUG - 1/4"F	ACRAC-X1/4F
TRIPLE X PLUG - 3/8"F	ACRAC-X3/8F

T Plugs



NAME	REFERENCE
DOUBLE T PLUG - 1/4"F	ACRAC-T1/4F
DOUBLE T PLUG - 3/8"F	ACRAC-T3/8F

Plugs for Tubes



NAME	REFERENCE
1/4"M PLUG	ACMANCHON1/4TUB10
3/8"M PLUG	ACMANCHON3/8TUB10

Adapters



NAME	REFERENCE
1/2"F - 3/4"M ADAPTER	ACADAPT1/2F3/4M
1/4"F - 3/8"M ADAPTER	ACADAPT1/4F3/8M
1/4"M - 3/8"M ADAPTER	ACADAPT1/4M3/8M ACMANCHON3/8TUB10
1/4"F - 3/8"F ADAPTER	ACADAPT1/4F3/8F
1/4"M - 3/8"F ADAPTER	ACADAPT1/4M3/8F ACMANCHON3/8TUB10

Caps



NAME	REF.
1/4" MALE CAP 6 Hexagon socket screw	ACBOUCH6PC1/4M
1/4" MALE CAP	ACBOUCH6P1/4M

Sleeve



NAME	REF.
1/4" FEMALE SLEEVE	ACMANCH1/4F1/4F

VACUUM MOULDING ANCILLARIES

ANCILLARIES & TOOLS

VACUUM CONTROL & REGULATION



ACREGUL-MAN-1/4-VACU

1/4" male vacuum regulator



ACREGUL-MAN-3/8

3/8" male vacuum regulator



ACVACU63-1/4MCUP

Vacuumeter
+ Suction cup

ACVACU63-1/4M

1/4" male
vacuumeter
Ø63 mm

ACVACU100-1/2M

1/2" male
vacuumeter
Ø100 mm

INFRARED THERMOMETER



MATHERMO/IR3

- ✓ Digital laser
- ✓ °C and °F values
- ✓ Measures the temperature of RTM equipment and resin before the injection starts.

ELECTRIC SCISSORS



MACUTTER/ELEC

2 serrated blades
+ Charger & Rechargeable battery

i
Perfect for cutting peel plies, films, bleeders, breathers and Vacuo Peel.

LEAK DETECTOR



MADETECT10

9V IEC 6LF22 Battery

Soft carrying case
215 x 50 x 40 mm

260 g

Adjustable sensibility 50 dB
Min. detectable sound pressure
1 nbar (in the 25-45 kHz range)
Without battery

BONDING EQUIPMENT



AUTOCLAVES



HOT DRAPE FORMERS



HOT BONDERS



IR LAMPS